

**AMENDMENTS TO THE CLAIMS**

**This listing of claims will replace all prior versions and listings of claims in the application:**

**LISTING OF CLAIMS:**

1. - ~~20.~~ 12. (canceled).

~~21.~~ 13. (currently amended): Use of a device for A method of measuring the quality and/or degradation of a fluid, for measuring the quality and/or the degradation of a food oil, said device including method comprising the steps of:

immersing a sensor ~~to be immersed in~~ said fluid oil to be measured, said sensor comprising at least one pair of electrodes spaced apart from each other and extending in substantially the same plane, each electrode of each pair of electrodes further having the shape of a comb ~~having a~~ having a plurality of substantially parallel teeth, the teeth of one of the electrodes being interdigitated with the teeth of the other electrode, the electrodes and said oil forming a measuring capacitive element whose capacitance varies as a function of the dielectric constant of the oil, said sensor ~~being capable of~~ providing an electrical output signal representative of said dielectric ~~constant, and constant,~~

~~processing means~~ receiving said output signal and ~~capable of~~ determining the degree of quality and/or degradation of said oil on the basis of said output signal; signal; and

wherein immersing both sides of the electrodes ~~are immersed in the fluid, oil,~~ on either side of said plane-plane, such that said oil can flow passing through said plane.

~~22.-14.~~ (currently amended): Use ~~according to claim 21 of said measuring device,~~  
wherein ~~The method according to claim 13, further comprising the step of providing~~ the sensor  
~~further includes with~~ a reference capacitive element, ~~element~~ comprising at least one pair of  
reference electrodes spaced apart from one another, said reference capacitive element being  
intended to be immersed in a reference oil, the ~~reference~~ electrodes and the reference fluid  
forming a reference capacitive element whose capacitance varies as a function of the dielectric  
constant of the reference oil, said reference capacitive element being capable of providing a  
reference signal representative of said reference dielectric constant to said processing means, and  
wherein the processing means are arranged for comparing the output signal to the reference  
signal.

~~23.-15.~~ (currently amended): Use ~~The method~~ according to claim ~~22-14, of said device,~~  
wherein the electrodes of said reference capacitive element extend in substantially the same  
plane and wherein both sides of the electrodes of said reference capacitive device are immersed  
in said ~~reference~~ oil, on either side of their plane, such that said ~~reference~~ oil can flow passing  
through said plane.

~~24.-16.~~ (currently amended): Use ~~The method~~ according to claim ~~22-14, of said device,~~  
wherein the reference fluid is arranged in an enclosed space insulated from said oil to be  
measured and in thermal contact with the latter, such that the reference oil has substantially the  
same temperature as said oil to be measured.

~~25.-17.~~ (currently amended): ~~Use The method~~ according to claim ~~24-16~~, of said device, wherein the enclosed space containing the reference oil is associated with a system for renewing said reference oil.

~~26.-18.~~ (currently amended): ~~Use The method~~ according to claim ~~25-17~~ of said device, wherein said renewal system comprises a reference oil tank in communication with said enclosed space and wherein said system comprises flow control means so as to allow regular renewal of the reference oil contained in said enclosed space.

~~27.-19.~~ (currently amended): ~~Use The method~~ according to claim ~~24-13~~, of said device, wherein the electrodes are respectively formed by flat plates.

~~28.-20.~~ (currently amended): ~~Use The method~~ according to claim ~~24-13~~, of said device, wherein the capacitive elements are surrounded by a metal frame forming a screen against electromagnetic interference.

~~29.-21.~~ (currently amended): ~~Use The method~~ according to claim ~~24-13~~, of said, wherein the electrodes of the capacitive elements are made from a food grade steel.

~~30.-22.~~ (currently amended): ~~Use The method~~ according to claim ~~24-13~~, of said device, wherein the electrodes of the capacitive elements are carried by an electrically insulating support structure having an aperture opposite a measuring region of said ~~electrodes~~ electrodes.

~~31.-23.~~ (currently amended): Cooking apparatus including a vat for containing a cooking fluid and heating means, wherein it further includes a device for measuring the quality and/or degradation of said cooking fluid, said measuring device including a sensor having at least one pair of electrodes spaced apart from each other and extending in substantially the same plane,

each electrode of each pair of electrodes further having the shape of a comb ~~having a~~ having a plurality of substantially parallel teeth, the teeth of one of the electrodes being interdigitated with the teeth of the other electrode, the electrodes and said cooking fluid forming a measuring capacitive element whose capacitance varies as a function of the dielectric constant of the fluid, said sensor being capable of providing an electrical output signal representative of said dielectric constant, and processing means for receiving said output signal and ~~capable of~~ determining the degree of quality and/or degradation of said cooking fluid on the basis of said output signal,

the measuring capacitive element being arranged in said vat such that both sides of its electrodes are immersed in the cooking fluid on either side of said plane of the electrodes so that said cooking fluid can flow passing through said plane.

~~32.~~24. (currently amended): Cooking apparatus according to claim ~~31~~,23, wherein the sensor further includes a reference capacitive element, including at least one pair of electrodes spaced apart from each other to be immersed in a reference fluid, the electrodes and the reference fluid forming a measuring capacitive element whose capacitance varies as a function of the dielectric constant of the reference fluid, said sensor being capable of providing an electrical output signal representative of said reference dielectric constant to said processing means and wherein the processing means are arranged for comparing the output signal to the reference signal.

~~33.~~25. (currently amended): Cooking apparatus according to claim ~~32~~,24, wherein the electrodes of said reference capacitive element extend in substantially the same plane and

wherein the both sides of the reference capacitive element electrodes are immersed in said cooking fluid on either side of said plane of the reference electrodes.

~~34.-26.~~ (currently amended): Cooking apparatus according to claim ~~32,24~~, wherein the reference fluid is arranged in an enclosed space insulated from the cooking fluid to be measured and in thermal contact with the latter, such that the reference fluid has substantially the same temperature as the cooking fluid to be measured.

~~35.-27.~~ (currently amended): Cooking apparatus according to claim ~~34,26~~, wherein the enclosed space containing the reference fluid is associated with a system for renewing said reference fluid.

~~36.-28.~~ (currently amended): Cooking apparatus according to claim ~~35,27~~, wherein said renewal system includes a reference fluid tank in communication with said enclosed space and wherein said system includes flow control means to allow regular renewal of the reference fluid contained in said enclosed space.

~~37.-29.~~ (currently amended): Cooking apparatus according to claim ~~34,23~~, wherein the electrodes are respectively formed by flat plates.

~~38.-30.~~ (currently amended): Cooking apparatus according to claim ~~34,23~~, wherein the capacitive elements are surrounded by a metal frame forming a screen against electromagnetic interference.

~~39.-31.~~ (currently amended): Cooking apparatus according to claim ~~34,23~~, wherein the electrodes of the capacitive elements are made from a food grade steel.

~~40.-32.~~ (currently amended): Cooking apparatus according to claim ~~31-23.~~, wherein the electrodes of the capacitive elements are carried by an electrically insulating support structure having an aperture arranged facing a measuring region of said electrodes.